

Color Copy

The leading uncoated colour laser printer paper for a wide range of uses, with FSC certification.

Color Copy gives you needle-sharp printouts and brilliant colours, especially with digital printing. Our range includes 8 different grammages in various formats, giving you a wide choice of applications. The perfect quality of the prints and the efficient colour reproduction will make your next presentation or mailing twice as successful.

Color Copy has been engineered for maximum performance on dry toner colour laser technologies, such as Kodak's NexPress presses.

Product features and benefits:



Forest Stewardship Council® certified



Manufactured to the international environmental standard, ISO 14001



Elemental Chlorine Free bleaching process



Guaranteed for laser and inkjet printing

Environmental statements:

When printing on Color Copy, you may wish to include a combination of the following environmental statements on your work. Color Copy :

- contains material sourced from responsibly managed forests, **certified in accordance with the FSC (Forest Stewardship Council)***
- is manufactured to the ISO 14001 international standard, minimising negative impacts on the environment

* Omit bold copy if your company or printer is not FSC certified

FSC logo usage guidelines:

The FSC logo can be used on publications printed on Color Copy. Should your company or printer have certification to the standard, you should use FSC MIX logo from the FSC Product Labelling Guide. An example is shown below:



Range specifications:

	A4 210x297	A3 420x297	457x305	SRA3 450x320	SRA2 450x640
90g/m ²	■	■		■	■
100g/m ²	■	■	■	■	■
120g/m ²	■	■	■	■	■
160g/m ²	■	■	■	■	■
200g/m ²	■	■	■	■	
250g/m ²	■	■	■	■	
300g/m ²				■	
350g/m ²				■	

- Available ream wrapped only

Product information continued overleaf...

Packaging specifications:

	A4	A3	SRA3		SRA2
	210x297	420x297	457x305	450x320	450x640
90g/m ²	500	500		500	500
100g/m ²	500	500	500	500	500
120g/m ²	500	500	500	500	500
160g/m ²	250	250	250	250	250
200g/m ²	250	250	200	250	
250g/m ²	250	250	200	250	
300g/m ²				125	
350g/m ²				125	

Quantity shown = ream wrapped

Technical specifications:

	Bulk	Caliper	Opacity	Brightness	Whiteness	Smoothness
		ISO534	ISO2471	ISO2470	ISO11475	ISO8791-2
	cm ³ /g	MIC	%	(D65) %	(CIE) %	(Bendtsen) ml/min
90g/m ²	1.06	95	90.0	110	157	30
100g/m ²	1.06	106	92.0	110	157	30
120g/m ²	1.05	126	95.0	110	157	30
160g/m ²	1.03	165	98.0	110	157	30
200g/m ²	1.0	200	99.0	110	157	30
250g/m ²	1.0	250	-	110	157	30
300g/m ²	1.06	318	-	110	157	40
350g/m ²	1.04	365	-	110	157	40