

Freeway Offset

An economical, hassle-free uncoated woodfree grade where simplicity and budget are key.

Freeway Offset is a no-nonsense white uncoated grade, ideal for standard litho printing. Available between 80 and 100g/m², the range works well with leaflet, flyers and direct mail applications.

Product features and benefits:



Accredited to the Programme for the Endorsement of Forest Certification schemes



Manufactured to the international environmental standard, ISO 14001



Suitable for laser and inkjet printing

Environmental statements:

When printing on Freeway Offset, you may wish to include a combination of the following environmental statements on your work. Freeway Offset :

- contains material sourced from responsibly managed forests, certified in accordance with the PEFC (Programme for the Endorsement of Forest Certification schemes)
- is manufactured to the ISO 14001 international standard, minimising negative impacts on the environment

PEFC logo usage guidelines:

The PEFC logo can be used on publications printed on Freeway Offset. Should your company or printer have certification to the standard, you can use the PEFC logo as outlined in the logo usage guidelines found in the PEFC information CD. An example of its use is shown below:



Range specifications:

	SRA2	SRA1
	450x640	640x900
80g/m ²	●	●
90g/m ²	●	●
100g/m ²	●	●

- Available ream wrapped and bulk packed on standard pallets

Packaging specifications:

	SRA2	SRA1
	450x640	640x900
80g/m ²	500 / 17k	500 / 8.5k
90g/m ²	500 / 16k	500 / 8k
100g/m ²	500 / 14k	250 / 7k

Quantity shown = ream wrapped / bulk packed

Product information continued overleaf...

Technical specifications:

	Bulk	Caliper	Opacity	Brightness	Whiteness
		ISO534	ISO2471	ISO2470	ISO11475
	cm ³ /g	MIC	%	%	(CIE) %
80g/m ²	1.35	108	92.0	91	145
90g/m ²	1.31	118	93.5	91	145
100g/m ²	1.32	132	95.0	91	145