

Giroform DEKA (reels)

Giroform, Howard Smith Paper Group's high performance carbonless paper range, has a reputation for copy quality, ease of use and environmental sensitivity that others just can't duplicate. Manufactured by Mitsubishi Paper Mills, one of Europe's most advanced paper producers, Giroform's microcapsule system generates the crispest, cleanest copies possible. Every detail of the original is preserved; nothing is added, nothing taken away.

Developed for customised, special applications, Giroform Deka products allow non-carbonless grades, such as a watermarked sheet, to be incorporated into a carbonless set. Giroform Deka CB can be combined with both non-carbonless and standard Giroform products. Both Deka grades have been developed to offer a sharp, stable, forgery-proof copy image, and their strength and stiffness help to keep presses running without a hitch.

Like all Giroform products – unlike any other range of carbonless paper – Giroform Deka carries the Nordic Swan environmental management mark.

Product features and benefits:



Forest Stewardship Council® certified



Manufactured to the international environmental standard, ISO 14001



Nordic Swan environmental accreditation

Associated qualities:

Giroform, Giroform ULTRA, Giroform ACCESSORIES

Environmental statements:

When printing on Giroform Deka, you may wish to include a combination of the following environmental statements on your work. Giroform Deka:

- contains material sourced from responsibly managed forests, **certified in accordance with the FSC (Forest Stewardship Council)***
- is certified with the Nordic Swan eco-label, ensuring it has been produced with methods that create minimum environmental impact
- is manufactured to the ISO 14001 international standard, minimising negative impacts on the environment

* Omit bold copy if your company or printer is not FSC certified

FSC logo usage guidelines:

The FSC logo can be used on publications printed on Giroform DEKA (reels). Should your company or printer have certification to the standard, you should use FSC MIX logo from the FSC Product Labelling Guide. An example is shown below:



Range specifications:

			235mm	255mm	310mm	345mm
55	White	3,500m	▲	▲		
CB 60	White	3,500m	▲	▲	▲	▲

▲ Available with 70mm cores, from stock for next day delivery