

# Pacesetter Silk

When you are producing volume print where cost and quality matter most, the choice is simple. Pacesetter's unique combination of quality and cost efficiency features make it the ideal choice for medium to long run print production. Both gloss and silk qualities benefit from high bulk and opacity, perform at high speed on press and are available in a comprehensive range of weights and sizes in both sheets and reels.

Pacesetter Silk combines ultimate value, performance and solid environmental credentials. Optimum visual performance with high opacity, Pacesetter's silk finish delivers consistent quality for both graphical and image reproduction and improved printing contrast.

## Product features and benefits:



Forest Stewardship Council® certified



Manufactured to the international environmental standard, ISO 14001



Totally Chlorine Free bleaching process



Pallets set at optimum heights to suit most in-feed systems



Delivered on flexi-pallets as standard, saving preparation time and money



Available from UK Wharf stocks



High bulk characteristics giving improved stability when running on high speed presses



Compatible for HP Indigo / Dry Toner digital technologies



Available in reels for CutStar applications

## Associated value based services:



Bulk packed only; the supply of customer specified quantities of paper, subject to agreement



MySize – Pacesetter Express; a 72 hour bespoke size service for orders over 3 tonnes

## Associated qualities:

Pacesetter Gloss

## Environmental statements:

When printing on Pacesetter Gloss, you may wish to include a combination of the following environmental statements on your work. Pacesetter Gloss :

- contains material sourced from responsibly managed forests together with recycled fibre, **certified in accordance with the FSC (Forest Stewardship Council)\***
- is manufactured to the ISO 14001 international standard, minimising negative impacts on the environment

\* Omit bold copy if your company or printer is not FSC certified

Product information continued overleaf...

**FSC logo usage guidelines:**

The FSC logo can be used on publications printed on think<sup>4</sup> bright. Should your company or printer have certification to the standard, you should use FSC MIX logo from the FSC Product Labelling Guide. An example is shown below:



**Range specifications:**

	*CutStar							Reels 880
	SRA3 320x450	SRA3 SG 450x320	SRA2 450x640	B2 520x720	630x880	SRA1 640x900	B1 720x1020	
90g/m <sup>2</sup>			○		●	●	●	
100g/m <sup>2</sup>			○		●	●		◇
115g/m <sup>2</sup>	■		○	■	●	●	●	◇
130g/m <sup>2</sup>	●		○	○	●	●	●	◇
150g/m <sup>2</sup>	●		○	○	●	●	●	◇
170g/m <sup>2</sup>	●		○	○	●	●	●	◇
200g/m <sup>2</sup>		■	○	■		●	●	
250g/m <sup>2</sup>		■	○	■		●	●	
300g/m <sup>2</sup>		■	○	■		●	●	
350g/m <sup>2</sup>		■	○	■		●	●	
400g/m <sup>2</sup>			○	■		●	●	

- Available ream wrapped and bulk packed on standard pallets
- Available ream wrapped and bulk packed on flexi-pallets
- Available ream wrapped only
- ◇ Available within 48 hours for orders over 5 tonnes

\*CutStar reels come with a 76mm core and 1200mm outer diameter

**Packaging specifications:**

	SRA3 320x450	SRA3 SG 450x320	SRA2 450x640	B2 520x720	630x880	SRA1 640x900	B1 720x1020
90g/m <sup>2</sup>			500 / 24k		250 / 14k	250 / 13k	250 / 11k
100g/m <sup>2</sup>			500 / 22k		250 / 12k	250 / 12k	
115g/m <sup>2</sup>	500		500	500	250 / 11k	250 / 11k	250 / 9k
130g/m <sup>2</sup>	500 / 36k		500 / 17k	500 / 15k	250 / 9k	250 / 9k	250 / 8k
150g/m <sup>2</sup>	500 / 32k		500 / 15k	250 / 13k	250 / 8k	250 / 8k	250 / 7k
170g/m <sup>2</sup>	500 / 28k		500 / 13k	250 / 12k	250 / 7.5k	250 / 7.5k	125 / 6k
200g/m <sup>2</sup>		250	250 / 10k	250			125 / 5k
250g/m <sup>2</sup>		250	250 / 8k	250			125 / 4k
300g/m <sup>2</sup>		250	125 / 6k	125			125 / 3.5k
350g/m <sup>2</sup>		250	125 / 7k	125			100 / 2.5k
400g/m <sup>2</sup>			125 / 5k	125			100 / 2.5k

Quantity shown = ream wrapped / bulk packed

Product information continued overleaf...

**Technical specifications:**

	Bulk	Caliper	Opacity	Brightness	Whiteness	Gloss
	ISO534	ISO534	ISO2471	D65/10	ISO11475	Tappi 75
	cm <sup>3</sup> /g	MIC	%	%	CIE %	%
90g/m <sup>2</sup>	0.87	78	92.0	99	122	30
100g/m <sup>2</sup>	0.87	87	93.0	99	122	30
115g/m <sup>2</sup>	0.84	94	94.5	99	122	30
130g/m <sup>2</sup>	0.84	111	95.5	99	122	30
150g/m <sup>2</sup>	0.84	128	97.0	99	122	30
170g/m <sup>2</sup>	0.84	145	98.0	99	122	30
200g/m <sup>2</sup>	0.88	176	99.0	99	122	30
250g/m <sup>2</sup>	0.83	225	99.0	99	122	30
300g/m <sup>2</sup>	0.88	287	99.0	99	122	30
350g/m <sup>2</sup>	0.96	337	99.0	99	122	30
400g/m <sup>2</sup>	0.92	380	99.0	99	122	30