

Purpose Offset

Purpose Offset is an everyday uncoated paper range that combines cost effectiveness with performance. It's available in the most frequent, essential sizes and weights with a matching board grade. Purpose Offset is also offered with press-ready Pallet Height to improve handling time. It's produced by a mill with ISO14001 environmental quality standard and has FSC certification too. Quick turnaround indent service is available.

Purpose Offset is a bulky, high in opacity sheet that keeps show-through to a minimum to add higher value to the finished jobs. Its smooth surface delivers quality print results for all your everyday work. Grade is laser and inkjet printing compatible.

Product features and benefits:



Forest Stewardship Council® certified



Manufactured to the international environmental standard, ISO 14001



Elemental Chlorine Free bleaching process



Pallets set at optimum heights to suit most in-feed systems



Delivered on flexi-pallets as standard, saving preparation time and money

Environmental statements:

When printing on Purpose Offset, you may wish to include a combination of the following environmental statements on your work. Purpose Offset :

- contains material sourced from responsibly managed forests, **certified in accordance with the FSC (Forest Stewardship Council)***
- is manufactured to the ISO 14001 international standard, minimising negative impacts on the environment
- is manufactured from pulp that has been bleached without the use of chlorine compounds using oxygen (elemental chlorine free), which are considered harmful to the environment

* Omit bold copy if your company or printer is not FSC certified

FSC logo usage guidelines:

The FSC logo can be used on publications printed on Purpose Offset. Should your company or printer have certification to the standard, you should use FSC MIX logo from the FSC Product Labelling Guide. An example is shown below:



Product information continued overleaf...

Range specifications:

	SRA2		SRA1				B1	
	450x640	630x880	880x630	640x880	640x900	650x920	700x1000	720x1020
70g/m ²	Δ			Δ	Δ		Δ	
80g/m ²	○	●	Δ	Δ	●	Δ	Δ	
90g/m ²	○	●			●		Δ	
100g/m ²	○	●			●		Δ	Δ
120g/m ²	Δ				Δ		Δ	
140g/m ²	○				●		Δ	
150g/m ²							Δ	
170g/m ²	○				●		Δ	
190g/m ²							Δ	
250g/m ²	○				●		Δ	
300g/m ²	○				●		Δ	

- Available ream wrapped and bulk packed on standard pallets
- Available ream wrapped and bulk packed on standard and flexi-pallets
- Δ Mill stocked items – delivered in 7 working days

Packaging specifications:

	SRA2		SRA1
	450x640	630x880	640x900
80g/m ²	500 / 19k	500 / 9.5k	500 / 9.5k
90g/m ²	500 / 17k	500 / 8.5k	500 / 8.5k
100g/m ²	250 / 16k	250 / 8k	250 / 8k
140g/m ²	250 / 11.5k		250 / 5.5k
170g/m ²	250 / 9.5k		250 / 4.5k
250g/m ²	125 / 6.25k		125 / 3.125k
300g/m ²	100 / 5k		100 / 2.5k

Quantity shown = ream wrapped / bulk packed

Technical specifications:

	Bulk	Caliper	Opacity	Brightness	Whiteness	Smoothness
		ISO534	ISO2471	ISO2470	ISO11475	DIN53108
	cm ³ /g	MIC	%	(D65/10)%	CIE	
80g/m ²	1.25	100	91.5	104	146	220
90g/m ²	1.25	112	93.0	104	146	220
100g/m ²	1.25	125	94.5	104	146	220
140g/m ²	1.22	171	98.0	104	146	220
170g/m ²	1.20	205	99.0	104	146	220
250g/m ²	1.20	301	>99.0	104	146	220
300g/m ²	1.20	361	>99.0	104	146	220