

# G Print Smooth

The G Print Family consists of white, wood-free coated papers that combine perfect readability with quality image reproduction capabilities. Strong, stiff and bulky, and renowned for high and consistent technical quality.

A wood-free, coated matt paper for demanding image reproduction, yet with significant bulk and stiffness - and a low reflecting surface which guarantees good readability.

## Product features and benefits:



Forest Stewardship Council® certified



\*Accredited to the Programme for the Endorsement of Forest Certification schemes (100% PEFC)



Manufactured to the international environmental standard, ISO 14001

\*When specified

## Associated qualities:

G Print Matt

## Environmental statements:

When printing on G Print Smooth, you may wish to include a combination of the following environmental statements on your work.  
G Print Smooth:

- is manufactured to ISO 14001 and EMAS (Eco-Management & Audit Scheme) international standards, minimising negative impacts on the environment

If the product has FSC or PEFC certification:

- contains material sourced from responsibly managed forests, **certified in accordance with the FSC (Forest Stewardship Council)\***
- contains material sourced from responsibly managed and sustainable forests, certified in accordance with the PEFC (Programme for the Endorsement of Forest Certification schemes)

\* Omit bold copy if your company or printer is not FSC certified

## FSC/PEFC logo usage guidelines:

The FSC logo can be used on publications printed on G-Print Smooth. Should your company or printer have certification to the standard, you should use FSC MIX logo from the FSC Product Labelling Guide. An example is shown below:



When specified, the PEFC logo can be used on publications printed on G Print Smooth. Should your company or printer have certification to the standard, you can use the PEFC logo as outlined in the logo usage guidelines found in the PEFC information CD. An example of its use is shown below:



Product information continued overleaf...

**Range specifications:**

	Availability
90g/m <sup>2</sup>	◆
100g/m <sup>2</sup>	◆
115g/m <sup>2</sup>	◆
130g/m <sup>2</sup>	◆
150g/m <sup>2</sup>	◆
170g/m <sup>2</sup>	◆
200g/m <sup>2</sup>	◆
230g/m <sup>2</sup>	◆
250g/m <sup>2</sup>	◆

- ◆ Special makings available, contact us for more information

**Technical specifications:**

	Bulk	Caliper	Opacity	Brightness	Whiteness	Smoothness
	ISO534:1995	ISO534	ISO2471	ISO2470	ISO11475	ISO 8791-4
	cm <sup>3</sup> /g	MIC	%	(D65) %	(CIE) %	(PPS) μm
90g/m <sup>2</sup>	0.91	82	92.0	97	119	1.8
100g/m <sup>2</sup>	0.91	91	94.5	97	119	1.8
115g/m <sup>2</sup>	0.93	107	96.0	97	119	1.8
130g/m <sup>2</sup>	0.96	125	97.0	97	119	1.8
150g/m <sup>2</sup>	0.97	145	98.0	97	119	1.8
170g/m <sup>2</sup>	0.97	165	>98.0	97	119	1.8
200g/m <sup>2</sup>	1.02	203	99.1	97	119	2.2
230g/m <sup>2</sup>	1.02	235	99.5	97	119	2.2
250g/m <sup>2</sup>	1.02	235	>99.5	97	119	2.2